



Luoyang JCB Bearing Technology Company Limited

HT10-30N1Z

SLEWING BEARING

FOUR-POINT CONTACT BALL SLEWING BEARING





Luoyang JCB Bearing Technology Company Limited

CONTENTS

01.

[MAIN SPECIFICATION](#)

02.

[TECHNICAL INFORMATION](#)

03.

[MANUFACTURE & INSPECTION](#)

04.

[PACKING AND STORAGE](#)

05.

[WARRANTY & CERTIFICATE](#)



Luoyang JCB Bearing Technology Company Limited

HT10-30N1Z

01

MAIN SPECIFICATION



[REFERENCE DRAWING](#)



[LUBRICATION](#)



[SPECIFICATION](#)



[BOLT HOLES TYPE & BOLTS](#)



[RAW MATERIAL](#)



[CORROSION PROTECTION](#)




Luoyang JCB Bearing Technology Company Limited

HT10-30N1Z

REFERENCE DRAWING

This drawing is reference for user, if user request for formal drawing , please contact with us: sales@jcb-bearing.com, the official drawing will be submitted to them.

01-1




01-2

Luoyang JCB Bearing Technology Company Limited

SPECIFICATION



HT10-30N1Z



Inner diameter (d): 24.160 in
 Outer diameter (D): 36.000 in
 Overall height (T): 3.500 in
 Outer ring height (H1): 3.000 in
 Inner ring height (H2): 3.000 in
 Weight: 411 lbs
 External bolt circle dia (J1): 33.250 in
 Number of bolt holes per hole circle (n1):24
 External bolt hole type : Selected by user
 External bolt hole diameter (N1): 0.813 in
 Internal bolt circle dia (J2): 27.250 in
 Number of bolt holes per hole circle (n2):30
 Internal bolt hole type : Selected by user
 Internal bolt hole diameter (N2): 0.813 in
 Tooth number (z):62
 Module of gear (DP):2.5
 Tooth width (B): 3.000 in